

24W Mini Amber LED Warning Beacon

FD24 Mini | Magnetic or Fixed Mount

Very low-profile beacon that mounts magnetically for temporary vehicle-to-vehicle use or bolts down permanently. Fitted to utes, trucks, plant machinery, pilot vehicles and OSOM vehicles.

SKU: FD24MINI (911 Signal) **Certifications:** SAE J845 Class 1; ECE R65 TA1 00 0064, TB1 00 0065 (as supplied)

24 x 1W
LED CONFIGURATION

47.5mm
LOW PROFILE

10-33V DC
VOLTAGE RANGE

IP68
INGRESS PROTECTION

SPECIFICATIONS

Lens	Reflex PMMA, 92 percent light transmittance
LED lifespan	100,000 hours
Beam angle	360 degree coverage
Flash patterns	8 selectable at 1-4Hz, including rotating and strobe modes
Control	On/off and pattern selection switch on the cigarette lighter plug
Cable	3m three-core (18AWG)
Mounting	Magnetic base (temporary) or bolt-down with supplied foam gasket (permanent)
Operating temperature	-30°C to +70°C
Housing	Aluminium alloy housing and top hat
Dimensions	110mm diameter x 47.5mm height
Warranty	UAGS Warning Light Warranty, 3-year limited coverage

OPERATION

On/off and flash pattern selection are controlled by the switch built into the cigarette lighter plug, so the beacon runs with no permanent wiring in magnetic use. For permanent bolt-down installation, wiring should be carried out by a qualified auto electrician.

DEPLOYMENT

Magnetic mounting suits temporary and vehicle-to-vehicle deployment on a clean, flat steel surface; the bolt-down option with foam gasket suits permanent fit-outs. Vehicle lighting requirements may vary by vehicle type, registration category, jurisdiction and intended use.

ORDERING

Available from UAGS (SKU FD24MINI); current pricing at uags.com.au. Trade accounts and bulk pricing available on request: (03) 8750 0926 or sales@uags.com.au.