380mm 42W Amber LED Magnetic Warning Minibar

LB380ATMM | Tinted Lens | Magnetic Mount

Amber LED warning minibar with a tinted lens, 18 flash patterns and a 3m plug-in cable with on/off and pattern switch on the plug. Mounts on 4 low-profile magnetic vacuum feet for temporary, no-drill use on utes and support vehicles.

SKU: LB380ATMM **Certifications:** ECE R65, ECE R10, SAE J845 Class 1



42 x 1W	18	10-30V DC	IP67
AMBER LEDS	FLASH PATTERNS	VOLTAGE RANGE	INGRESS PROTECTION

SPECIFICATIONS

Model	LB380ATMM (LED Autolamps)
Lens and Base	Tinted polycarbonate lens with amber LEDs, ABS base
LED Configuration	42 x 1W LEDs, 360 degree omnidirectional output, 30,000 hour LED lifespan
Voltage Range	Multivolt 10-30V DC (12V and 24V vehicle systems)
Current Draw	2.51A @ 13.8V DC
Mounting	4 low-profile magnetic vacuum feet; temporary use, supplier-rated to 100km/h maximum. Optional four-point adjustable mounting feet kit (LED Autolamps 246BKT) for fixed installation
Cable	3m with power plug; on/off and pattern selection switch on the plug
Ingress Protection	IP67, -40 to +60 degrees C operating range
Dimensions	380mm x 171mm x 49mm
Certifications	ECE R65 and R10 compliant (ECE R65 patterns 12-15); SAE J845 Class 1 compliant (pattern 9)
Warranty	LED Autolamps manufacturer warranty, 5 years (full terms on the product page)

FLASH PATTERNS

1	Rotating (slow), 75 FPM	**10**	Quint (all), 75 FPM
2	Rotating (fast), 146 FPM	**11**	Steady Half, 75 FPM
3	Single (split), 75 FPM	**12**	Single 2Hz, 123 FPM (ECE R65)
4	Double (split), 75 FPM	**13**	Double 2Hz, 123 FPM (ECE R65)
5	Triple Flash (split), 122 FPM	**14**	Triple 2Hz, 123 FPM (ECE R65)
6	Quad (split), 75 FPM	**15**	Quad 2Hz, 123 FPM (ECE R65)
7	Single (all), 75 FPM	**16**	Hyper-Flash (split), 81-500 FPM
8	Double (all), 75 FPM	**17**	Mega-Flash (split), 61 FPM
9	Quad (all), 75 FPM (J845 Class 1)	**18**	Steady (all)

WIRING AND OPERATION

Plug-in operation with no permanent wiring. On/off and flash pattern selection are controlled from the power plug. Affix to a clean, flat roof surface, parallel to the ground. The magnetic mount is intended for temporary use at speeds not exceeding 100km/h.

DEPLOYMENT

Used for temporary and vehicle-to-vehicle warning lighting on utes, support vehicles and pool or hire vehicles. For permanent installations use the 246BKT mounting feet kit or a fixed-mount bar. Vehicle lighting requirements may vary by vehicle type, registration category and jurisdiction.

ORDERING	Available from UAGS (SKU LB380ATMM); current pricing at uags.com.au. Trade accounts and bulk pricing available on request: (03) 8750 0926 or sales@uags.com.au.