

No U Turn (SYM)

Corflute Sign Panel

No U Turn (SYM) (600x600mm) standard-derived regulatory corflute signface panel with No U Turn symbol on Class 400T retroreflective white sheeting. Supplied as a modular corflute panel for compatible temporary roadwork sign frame systems.

SKU: CF66NUT



600 x 600mm

PANEL SIZE

Class 400T

REFLECTIVE SHEETING

6mm Corflute

UV STABILISED SUBSTRATE

Standard-Derived

SIGNFACE DESIGN

SPECIFICATIONS

Product Type	Corflute traffic sign panel
Panel Classification	Standard-derived regulatory signface panel
Sign Series	No verified RM-series corflute sign series supplied
Corflute Sign Code	No verified corflute sign code supplied for this product
Related Metal Sign Reference	R2-5B aluminium / metal road sign reference for 600x600mm No U Turn signface identification only; not the corflute product code
State / Legacy Reference	No verified state or legacy reference supplied
Signface Context	Standard-derived No U Turn regulatory signface layout based on related R2-5B 600x600mm signface identification context.
Legend / Symbol	No U Turn symbol
Signface Colours	Black U-turn arrow symbol with red annulus and diagonal slash on white retroreflective background, with black border
Panel Size	600x600mm
Panel Thickness	6mm
Reflective Sheeting	Class 400T retroreflective white sheeting with printed black and red signface elements
Substrate	6mm UV stabilised corflute
Frame Compatibility	Compatible with suitable temporary roadwork sign frame systems that accept 600x600mm corflute panels, including suitable Multi-Message Sign Frame No. 1 and 600x600mm Double-Sided Traffic Sign Frame Type 5 arrangements where the frame configuration and sign arrangement are suitable
Use Context	Temporary traffic management, site access control and turn-restriction arrangements where a No U Turn message is specified by the applicable TMP, TGS, project requirements, site traffic management arrangement, facility requirements or relevant authority requirements
Warranty	UAGS Corflute Sign Warranty, 1-year limited coverage

TYPICAL USE

May be used for temporary road closures, changed intersection arrangements, median openings, temporary one-way arrangements, detours, access control points, car parks, depots, construction compounds, industrial facilities and worksite traffic management setups where specified.

DEPLOYMENT

Selection, placement, panel pairing, visibility, frame arrangement and use remain subject to the applicable TMP, TGS, site traffic management arrangement, facility requirements, project requirements, site conditions and relevant authority requirements.

ORDERING

Available from UAGS (SKU CF66NUT); current pricing at uags.com.au. Trade accounts and bulk pricing available on request: (03) 8750 0926 or sales@uags.com.au.