

12W Amber LED Warning Beacon

U4-12 Low Profile | 18 Flash Patterns

The low-profile beacon in the U4 series: 148mm diameter and just 64mm high, sharing its base and functions with the higher-output U4-24. Fitted to utes, trucks, forklifts and plant machinery where installed height matters.

SKU: U4-12-AAT **Certifications:** ECE R65, SAE Class 2 (as supplied)

12 x 1W
LED CONFIGURATION

64mm
LOW PROFILE

10-30V DC
VOLTAGE RANGE

IP65
INGRESS PROTECTION

SPECIFICATIONS

Lens	Amber polycarbonate
Beam angle	360 degree coverage
Current draw	1.3A maximum @ 13.8V DC (flashing mode)
Functions	Pattern selection, dimming and synchronisation via function wires
Mounting	Aluminium three-point base, mounting gasket included
Weight	0.5kg
Dimensions	148mm diameter x 64mm height
Warranty	UAGS Warning Light Warranty, 3-year limited coverage

WIRING AND OPERATION

Installation by a qualified auto electrician. Connect to a separate, fused circuit.

Red / Black	Positive supply (5A fuse recommended) / chassis ground.
Blue wire	Pattern select (touch to ground): 1s = next; 2-3s = previous; 4s = default; 5s = dim mode; 8s = off.
Yellow wire	Join across units to synchronise.
White wire	Connect to positive to dim.

FLASH PATTERNS

1-2	ECE Single Flash, 120 FPM, Ph1/Ph2	11-12	SAE Double Flash, 75 FPM, Ph1/Ph2
3-4	ECE Double Flash, 120 FPM, Ph1/Ph2	13-14	SAE Quad Flash, 75 FPM, Ph1/Ph2
5-6	ECE Quad Flash, 120 FPM, Ph1/Ph2	15-16	SAE Rotate Flash, 75 FPM, Ph1/Ph2
7-8	ECE Rotate Flash, 120 FPM, Ph1/Ph2	17	Steady On
9-10	SAE Single Flash, 75 FPM, Ph1/Ph2	18	Off

ORDERING

Available from UAGS (SKU U4-12-AAT); current pricing at uags.com.au. Trade accounts and bulk pricing available on request: (03) 8750 0926 or sales@uags.com.au.