

Adjustable Warning Light Window Mount

WM-155-30 | Fits Light Heads up to 122mm | 30° Adjustable | 3M Adhesive

Interior window mount that fits a standard surface mount warning light head to the inside of a front, side or rear vehicle window, projecting the warning light outward through the glass without drilling the dash or bodywork. The angled housing shrouds the head from the cabin to limit glare and driver distraction. The head fits to a supplied back plate, seats on washered acorn nuts running in curved slots, and the assembly bonds to clean interior glass with factory-applied 3M double-sided adhesive tape.

SKU: WM-155-30 **Confirmed fitment:** UAGS U30-12A Ultra-Slim LED Warning Light Head (sold separately)



122mm

MAXIMUM HEAD WIDTH

30°

ADJUSTABLE ANGLE

3M

ADHESIVE TAPE FIXING

ABS

HOUSING MATERIAL

SPECIFICATIONS

Model	WM-155-30
Product Type	Interior window mount for surface mount warning light heads
Material	ABS plastic, black
Fixing Method	Factory-applied 3M double-sided adhesive tape to interior glass
Maximum Head Width	Holds surface mount warning light heads up to 122mm wide
Angle Adjustment	Up to 30 degrees, via washered acorn nuts running in curved slots on the rear housing
Dimensions	154.5(L) x 78.4(W) x 91(H)mm
Mounting Positions	Front, side or rear vehicle windows, interior side of the glass
Confirmed Fitment	UAGS U30-12A Ultra-Slim LED Warning Light Head (sold separately)
Care	Clean with a damp cloth or mild soapy water; avoid solvents and harsh chemical cleaners
Warranty	Manufacturer Warranty - 12 Months

INCLUDED IN THE BOX

Window mount with 3M double-sided adhesive	x 1	M4 x 0.7 12L outer hex screws	x 2
Back plates for light head modules	x 3	M4 hex nuts	x 2
M4 x 0.7-8L cross screws	x 2	Washers and acorn nuts	x 2

The warning light head is sold separately. Confirmed fitment is the UAGS U30-12A; contact UAGS to confirm fitment for other surface mount heads within the 122mm limit.

INSTALLATION

Assemble the module

1. Fit the M4 outer hex screws and hex nuts to the back plate.
2. Secure the light head to the back plate with the M4 cross screws.
3. Press the assembled module into the mount and secure it with the washers and acorn nuts.

Fit to the glass

1. Peel the backing off the 3M double-sided adhesive.
2. Press the mount onto clean interior glass and hold for at least 30 seconds.
3. Loosen the rear acorn nuts and slide the module within the curved slots to set the angle (up to 30 degrees).
4. Tighten the acorn nuts to lock the angle.

Care: clean with a damp cloth or mild soapy water only. Solvents and harsh chemical cleaners can cause premature cracking or discolouration of the plastic.

DEPLOYMENT

Puts interior directional warning on traffic control utes, TMA support vehicles, pool and hire vehicles and fleet cars where drilling panels or bodywork is not an option. Mounts to front, side or rear windows on the interior side of the glass, with the angle adjustment aiming output correctly through raked glass.

Covers the interior warning role of sealed dash light and visor kit units with one practical difference: the light head is a separate, interchangeable part, so a damaged head or mount is replaced on its own rather than as a complete kit.

Pair with the UAGS U30-12A Ultra-Slim head (12W amber, 19 flash patterns, sold separately). Vehicle lighting requirements may vary by vehicle type, registration category and jurisdiction.

ORDERING

Available from UAGS (SKU WM-155-30); current pricing at uags.com.au. Trade accounts and bulk pricing available on request: (03) 8750 0926 or sales@uags.com.au.